

KOHLER®

Roughing-In

K-2826
IRON/TONES™
DROP-IN/UNDER-MOUNT BATHROOM SINK

Product Information

Applicable product:		
K-2826	Drop-in/Under-mount bathroom sink	
Accessories/hardware:		
P-trap	K-9018	Recommended
Fixture*:	Basin area	Water depth
Bathroom sink	23-3/4" (603 mm) x 14-1/2" (368 mm)	3-7/8" (98 mm)
Drain hole	Ø 1-3/4" (44 mm)	
* Approximate measurements for comparison only.		
Included components:		
Basin clamp assembly	52047	
Cut-out template	1053506-7	

Installation Notes

Install this product according to the installation guide.

Supplied basin clamp assemblies require 1" (25 mm) minimum countertop thickness. Installer must supply anchors for thinner countertops.

NOTICE: The countertop manufacturer or cutter **must** use the cut-out template provided with the product, or a current one provided by the Kohler Co. (call 1-800-4-KOHLER.) Kohler Co. is not responsible for cut-out errors when the incorrect cut-out template is used.

Will comply with **ADA** when installed per Section 606 Lavatories of the Act.

For under-mount installation, counter top thickness can not be greater than 1" (25 mm) for **ADA** compliance.

Fixture conforms to standard ASME A112.19.1/CSA B45.2. All dimensions are nominal.

