

### Product Information

Applicable product:	
Comfort Height Class Five Toilet, left-hand trip lever (shown)	K-3946
Comfort Height Class Five Toilet, right-hand trip lever	K-3946-RA

Fixture:	
Configuration	one-piece, elongated
Water per flush	1.28 gpf (4.8 lpf)
Passageway	2-1/8" (54 mm)
Water area	11" (279 mm) x 7-3/4" (197 mm)
Water depth from rim	6-1/16" (154 mm)
Seat post hole centers	5-1/2" (140 mm)

Included components:	
Tank cover	1180586
Trip lever, left-hand	K-9466-L <b>OR</b>
Trip lever, right-hand	K-9466-R
Toilet seat	K-4636
Tank accessory pack	52265
Bolt cap accessory pack	52048

### Installation Notes

Install this product according to the installation guide.

Will comply with the Americans with Disabilities Act (**ADA**) when installed per the requirements of the 2010 ADA Standards for Accessible Design, Section 604 Water Closets and Toilet Compartments, of the Act. The Model Plumbing Codes require the installation of elongated open-front toilet seats in public bathrooms.

Will comply with **CSA B651** when installed per Clause 4.3.6 of the standard.

Will comply with **OBC** when installed per Clause 3.8.3.8 and 3.8.3.9.

Fixture conforms to ASME Standard A112.19.2/CSA B45.1. All dimensions are nominal.

