

# KOHLER® Roughing-In

**K-1834  
UNDERScore®  
DROP-IN BATH**

## Product Information

|   |  |
|---|--|
| Applicable product:                             |  |
| Drop-in bath                                    | K-1834                                 |
| Fixture*:                                       |  |
| Bathing well:                                   |  |
| Basin area, bottom                              | 45-3/4" (1162 mm) x 25-15/16" (659 mm) |
| Basin area, top                                 | 65-3/8" (1661 mm) x 29-5/16" (745 mm)  |
| Weight  | 82 lbs (37.2 kg)                       |
| To overflow:                                    |  |
| Water depth                                     | 19-7/16" (494 mm)                      |
| Capacity  | 112.9 gal (427 L)                      |
| * Approximate measurements for comparison only. |  |
| Drop-in cut-out                                 | 71-1/2" (1816 mm) x 35-1/2" (902 mm)   |

|  |        |
|--|--------|
| Required accessories:                                |        |
| Clearflo slotted overflow brass bath drain <b>OR</b> | K-7271 |
| Clearflo slotted overflow bath drain – PVC pipe      | K-7272 |
| Optional accessories:                                |        |
| Undermount kit                                       | K-593  |
| Pillow   | K-1491 |
| Footstop   | K-1601 |

## Installation Notes

Install this product according to the installation guide.

Floor support under bath must provide for a minimum of 58 lbs/square foot (285 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

Fixture conforms to ANSI Standards Z124.1.2. All dimensions are nominal.

No change in measurement if connected with drain illustrated. (K-7272)

