

# KOHLER® Roughing-In

K-13462, K-13463  
ELECTRONIC FAUCET

## Product Information

Applicable product:	
Electronic faucet – with mixer	K-13462
Electronic faucet – without mixer	K-13463

Required accessories:	
AC single supply transformer	K-13480
AC multi-outlet power supply (up to 8 faucets)	K-13481
AC supply 4' (1.2 m) cable assembly <b>OR</b>	K-13487
AC supply 6' (1.8 m) cable assembly <b>OR</b>	K-13602
AC supply 8' (2.4 m) cable assembly <b>OR</b>	K-13603
AC supply 10' (3 m) cable assembly	K-13604

Optional accessories:	
Grid drain with overflow	K-7129-A
Grid drain without overflow	K-7129
4" (102 mm) escutcheon plate – round	K-13478-A
8" (203 mm) escutcheon plate – round	K-13479-A
Thermostatic mixing valve	K-13601

Medium Spray 0.35 gal/min (1.32 l/min) – Insert only	1160595
Additional flow options are available (refer to the Price Book)	—

## Installation Notes

Install this product according to the installation guide.

A 1-1/4" (32 mm) minimum to 1-1/2" (38 mm) maximum diameter mounting hole is required.

The minimum distance between the back of the faucet spout and the wall must be 1-3/4" (44 mm). This will allow proper clearance for setscrew access.

The maximum distance between the bathroom sink basin edge to the base of the faucet spout must be 1-3/4" (44 mm).

The maximum height of the lip basin should be 3/4" (19 mm).

Product includes 0.5 gal/min (1.9 l/min) rosebud spray aerator. Other aerator styles are available. Please contact your distributor or see Kohler.com.

This product requires an AC power supply (not included).

**ADA, ICC/ANSI A117.1, CSA B651, OBC** compliant when installed to the specific requirements of these regulations.

