

Product Information

| | |
|---|-----------|
| Applicable faucet trim: | |
| Wall-mount bathroom sink faucet trim – 9-3/4" (248 mm) spout reach | K-T343-4M |
| Wall-mount bathroom sink faucet trim – 9-3/4" (248 mm) spout reach, white handle inserts | K-T343-4P |
| Wall-mount bathroom sink faucet trim – 11-3/4" (298 mm) spout reach | K-T344-4M |
| Wall-mount bathroom sink faucet trim – 11-3/4" (298 mm) spout reach, white handle inserts | K-T344-4P |
| Lever handle is ADA compliant ADA | |
| Required accessories: | |
| Two-handle ceramic valve | K-410-K |
| Optional accessories: | |
| Under-mount pop-up bathroom sink drain with tailpiece OR | K-7114 |
| Touch activated bathroom sink drain with tailpiece OR | K-7124 |

| | |
|---|--------|
| Bathroom sink drain with non-removable metal stopper and tailpiece – 3" rough OR | K-7127 |
| Bathroom sink grid drain with tailpiece | K-7129 |
| Additional flow options are available (refer to the Kohler Price Book) | — |

Installation Notes

Install this product according to the installation guide.

A minimum of 1-1/2" (38 mm) to 6" (152 mm) clearance space must be maintained between the bottom of the spout and the top of the fixture rim.

Three 1-1/2" (38 mm) diameter cut-out holes are required for the spout and handles.

Lower flow aerator options are available. Please refer to the Kohler Price Book.

