

KOHLER® Roughing-In

K-T14420, K-T14421, K-T14422, K-T14423 PURIST® BATH & SHOWER TRIM SET

Product Information

Applicable faucet trim only:	
Bath and shower cross handle* (shown)	K-T14420-3
Bath and shower lever handle*	K-T14420-4
Shower cross handle*	K-T14421-3
Shower lever handle*	K-T14421-4
Shower only trim, cross handle	K-T14422-3
Shower only trim, cross handle	K-T14422-4
Non-diverter valve cross handle*	K-T14423-3
Non-diverter valve lever handle*	K-T14423-4
Valve W/diverter only trim, cross handle	K-T14501-3
Valve W/Diverter only trim, lever handle	K-T14501-4
35° Bath spout	K-14426
90° Bath spout	K-14427

*Rite-Temp® valve must be ordered to complete faucet.

Required accessories:	
Rite-Temp® valve OR	K-304-*
HiFlow Rite-Temp valve with stops OR	K-2971-KS
Rite-Temp valve with diverter OR	K-11748-K
Rite-Temp valve with diverter and stops	K-11748-KS

* For a complete listing of all the Rite-Temp valves, refer to the K-304-* Specification Sheet or Roughing-In Sheet.

Optional accessories:	
HiFlow Rite-Temp® thin wall installation kit	88526
Deep roughing-in kit for Rite-Temp® valve (lever and cross handles)	1016154

Installation Notes

Install this product according to the installation guide.

NOTICE: Risk of product damage. Long screws, for installing trim, can damage the K-2971-KS valve. Consult the trim installation guide to verify if the thin wall installation kit (88526) is needed.

Install this product according to the installation guide.

Avoid cross-flow conditions. Do not install shut-off device on either valve outlet.

Cap shower outlet if deck-mount spout, diverter, or handshower is connected to spout outlet.

Install straight pipe or tube drop of 7" (178 mm) to 18" (457 mm) with single elbow between valve and wall-mount spout.

